



HYDRO-STAT, INC.

Aluminum SCBA Cylinders

Features & Benefits



- All aluminum construction
- Extremely durable
- Cost effective long term cylinder solution
- 5-year hydrostatic retest
- Unlimited life potential
- Available in a 30 minute, 2216 psi format
- USDOT & Transport Canada approved
- Compatible with most 2216 psi cylinder valves
- Available in yellow or white
- Compatible with all major model low pressure SCBA

Safety + Reliability + Savings = SCI

Aluminum SCBA Cylinders

Specifications



ALUMINUM SCBA CYLINDER SPECIFICATIONS

Model	Approx. Duration (min.)*	DOT Approval	TC Approval	PSI	Bar	Volume cu. in. (min.)	Volume liter (min.)	OD inches	OD MM (max.)	OAL inches (max.)	OAL MM (max.)	Weight LBS	Weight KG	Port
DFP0072	30	3AL	3ALM	2216	153	516	8.45	6.9	175.2	20.56	522.22	17.45	7.92	.750-16 UNF 2B

*Specifications are approximate and subject to change without notice. "Approx. Duration (min)" is common industry jargon and is intended to draw a comparison to competitive products only. Duration specifications should not be considered as literal as the duration of each cylinder is predicated on the breathing rate of the user.



HYDRO-STAT, INC.

mickels@hydrostat.com
 1111 SW 1st Way • Deerfield Beach, FL 33441
 954.428.7677